



Tubular Motor

MM-59R



Ø 59

Diameter 59mm



| Mechanical Limit Switch

| Build-In Receiver

| Precise Setting of Limit Positions

| 5-Year Warranty

| Stable Performance

| Low Noise

| Easy To Install



Technical Data

Model	Torque	Speed	Voltage	Frequency	Power	Current	Degree of Protection	Running Time
MM59R-60/15	60N.m	15rpm	230V/120V	50Hz/60Hz	400W	1.7A	IP44	4min
MM59R-80/15	80N.m	15rpm	230V/120V	50Hz/60Hz	450W	2A	IP44	4min
MM59R-100/12	100N.m	12rpm	230V/120V	50Hz/60Hz	440W	1.9A	IP44	4min
MM59R-100/15	100N.m	15rpm	230V/120V	50Hz/60Hz	440W	1.9A	IP44	4min
MM59R-120/9	120N.m	9rpm	230V/120V	50Hz/60Hz	445W	1.9A	IP44	4min
MM59R-120/12	120N.m	12rpm	230V/120V	50Hz/60Hz	445W	1.9A	IP44	4min
MM59R-120/15	120N.m	15rpm	230V/120V	50Hz/60Hz	445W	1.9A	IP44	4min
MM59R-140/3	140N.m	3rpm	230V/120V	50Hz/60Hz	500W	2.2A	IP44	4min
MM59R-140/9	140N.m	9rpm	230V/120V	50Hz/60Hz	500W	2.2A	IP44	4min
MM59R-140/12	140N.m	12rpm	230V/120V	50Hz/60Hz	500W	2.2A	IP44	4min
MM59R-140/15	140N.m	15rpm	230V/120V	50Hz/60Hz	525W	2.3A	IP44	4min
MM59R-160/9	160N.m	9rpm	230V/120V	50Hz/60Hz	505W	2.2A	IP44	4min
MM59R-180/7	180N.m	7rpm	230V/120V	50Hz/60Hz	485W	2.1A	IP44	4min
MM59R-180/9	180N.m	9rpm	230V/120V	50Hz/60Hz	500W	2.2A	IP44	4min
MM59R-190/9	190N.m	9rpm	230V/120V	50Hz/60Hz	545W	2.4A	IP44	4min